


## QUAD

Tool Ref.	LPI	Depth	Min. Volume	Max. Volume	
63	-	200	31.6	6.63	7.53
106	-	200	40.6	8.35	9.49
90	-	180	36.7	9.14	10.39
33	-	180	49.0	14.20	16.13
13	-	165	55.0	14.23	16.17
71	-	150	55.2	14.09	16.01
204	-	150	80.8	18.24	20.73
18	-	140	81.5	22.82	25.93
15	-	125	147.3	12.67	14.40
43	-	120	78.2	16.95	19.26
16	-	130	78.0	19.05	21.65
94	-	120	94.8	19.74	22.43
35	-	110	89.2	18.27	20.77
46	-	110	87.6	20.25	23.01
12	-	100	134.0	27.31	30.34
7	-	95	106.7	29.06	32.29
55	-	85	102.2	27.09	30.10
152	-	85	117.3	29.18	32.42
47	-	75	139.0	34.84	38.71
8	-	70	133.5	26.18	29.09
33	-	65	106.2	35.16	39.07
54	-	65	186.3	43.32	48.13
77	-	55	133.7	39.53	43.92
51	-	55	210.0	48.36	53.73
153	-	45	172.0	48.19	53.55
65	-	45	173.0	53.04	58.93
159	-	35	186.0	60.25	66.94
24	-	35	235.0	75.94	84.38
73	-	30	215.0	80.07	88.96
90	-	25	382.0	84.70	94.11
11	-	25	315.0	95.10	105.67
68	-	20	365.0	128.86	143.18
42	-	17	425.0	149.21	165.79
48	-	16	675.0	168.48	188.31
86	-	10	375.0	156.93	174.37
78	-	10	500.0	189.62	210.69

### QUAD



Lower solid applications,  
tight coat-weight  
tolerances