

TRI-HELICAL

Tool Ref.	LPI	Depth	Min. Volume	Max. Volume	
6	-	200	19.2	5.13	5.83
118	-	200	31.1	7.63	8.67
95	-	180	33.2	8.38	9.52
58	-	180	36.6	10.69	12.15
102-F	-	180	60.4	16.18	18.39
34	-	150	53.0	15.23	17.31
108-F	-	145	90.2	23.71	26.94
67	-	140	37.5	10.29	11.69
23	-	120	55.3	14.36	16.31
22	-	120	69.2	20.45	23.24
49	-	110	69.2	19.19	21.81
107	-	100	55.7	15.53	17.26
11	-	100	85.8	24.27	26.97
47	-	95	94.6	28.35	31.50
85	-	90	95.9	27.67	30.74
39	-	85	99.9	28.91	32.12
8	-	80	115.6	35.00	38.89
3	-	75	167.1	57.71	64.12
62	-	70	130.4	36.17	40.19
84	-	64	132.5	37.56	41.74
29	-	60	140.4	40.10	44.56
88	-	60	157.8	43.84	48.71
43	-	55	167.0	47.85	53.17
38	-	50	194.0	57.00	63.33
27	-	45	174.0	51.05	56.72
12	-	45	200.0	57.25	63.61
54	-	42	187.0	52.25	58.05
61	-	38	166.0	47.90	53.22
83	-	35	275.0	76.43	84.92
55	-	35	295.0	86.23	95.81
62	-	30	247.0	77.39	85.99
75	-	30	310.0	89.59	99.54
23	-	28	385.0	114.07	126.74
26	-	25	377.0	68.13	75.70
68	-	23	195.0	76.11	84.57
101	-	20	340.0	116.36	129.29
65	-	10	676.0	195.95	217.72

TRI HELICAL



High solid large particle applications. TH's offer highest transfer characteristics